

MACHINE GALAXY TP (TRANSPALLET)

PALLET WRAPPING MACHINE WITH STRETCH FILM
 WITH OPENING ON THE PLATE TO LOAD WITH TRANSPALLET

SPECIFICATIONS

display touch screen 7" color
 machine controlled by PLC
 siemens frequency converters on all the motors
 machine power 1,75 kw
 machine supply 220-240 VAC 1 ph, 50-60 Hz
 turntable diameter 1650 mm (max pallet 1200x100 mm)
 max pallet weight 2100kg
 Beeper on cycle start
 table phase stop
 photocell on the loading area to inhibit start in the event of obstacles
 pallet height sensing with photocell
 pallet height also settable by the panel
 n° 99 custom programs
 upward speed adjust
 downward speed adjust
 speed rotation adjust
 management of the film tension and percentage of pre-stretch
 bottom rounds adjust
 top rounds adjust
 photocell delay adjust



only up cycle
 only down cycle
 up and down cycle
 up and down cycle alternate
 cycle with reinforcement at pre-set height
 cycle with start at pre-set height
 top sheet cycle
 possibility to set a protection password on parameters
 machine diagnostic by display
 possibility to change the load position: front, side right or side left (front position is the standard if not otherwise specified)

available wrapping heights:
 2000 = H 2000 mm (with film coil h500 mm)
 2400 = H 2400 mm (with film coil h500 mm)

available film coil carriages:
 FM : mechanical friction and manual film tension adjust
 FE : electromagnetic brake and film tension adjust by control panel
 PM : power pre-stretch fix 230% (other on demand) and film tension adjust by control panel
 PMV : power pre-stretch adjustable up to 230% (other on demand). Separated adjust of tension and pre-stretch by control panel

