


MACHINE	ROLLERTECH-E
PALLET WRAPPING MACHINE WITH STRETCH FILM	
SPECIFICATIONS	
display touch screen 7" color	
machine controlled by PLC	
Hi frequency battery charger 110-240 VAC, 50-60 Hz	
battery charger power 0,4 kw	
machine supplied by n° 2 in AGM 12V, 85Ah (12+12 = 24VDC)	
battery autonomy 100 pallet (80 pallet for version PM)	
<i>(autonomy is related to a wrapping with a duration of one minute)</i>	
Beeper on cycle start	
machine weight 300kg	
pallet height sensing with photocell	
pallet height also settable by the panel	
n° 99 custom programs	
upward speed adjust	
downward speed adjust	
speed rotation adjust	
bottom rounds adjust	
top rounds adjust	
photocell delay adjust	
only up cycle	
only down cycle	
up and down cycle	
cycle with reinforcements at pre-set heights	
cycle with start at pre-set height	
top sheet cycle	
possibility to set a protection password on parameters	
machine diagnostic by display	
monitoring of the battery charger from the display	
distance from pallet 110 cm	
available wrapping heights:	
2000 = H 2000 mm (with film coil h500 mm)	
2400 = H 2400 mm (with film coil h500 mm)	
available film coil carriages:	
FM : mechanical friction and manual film tension adjust	
FE : electromagnetic brake and film tension adjust by control panel	
PM : power pre-stretch fix 200% (other on demand) and film tension adjust by control panel	
<div style="display: flex; justify-content: space-around;"> <div style="text-align: center;">  <p>FM</p> </div> <div style="text-align: center;">  <p>FE</p> </div> <div style="text-align: center;">  <p>PM</p> </div> </div> <div style="display: flex; justify-content: space-around; margin-top: 10px;"> <div style="text-align: center;">  </div> <div style="text-align: center;">  <p>TOUCH SCREEN</p> </div> <div style="text-align: center;">  <p>TOUCH SCREEN</p> </div> </div>	

