

MACHINE ROLLERTECH

PALLET WRAPPING MACHINE WITH STRETCH FILM

SPECIFICATIONS

display touch screen 7" color

machine controlled by PLC

Hi frequency battery charger 110-240 VAC, 50-60 Hz

battery charger power 0,4 kw

machine supplied by n° 2 in AGM 12V, 130Ah (12+12 = 24VDC)

battery autonomy 140 pallet (110 pallet per vers. PM, PMV)

(autonomy is related to a wrapping with a duration of one minute)

Beeper on cycle start

machine weight 380kg

pallet height sensing with photocell

pallet height also settable by the panel

n° 99 custom programs

upward speed adjust

downward speed adjust

speed rotation adjust

bottom rounds adjust

top rounds adjust

photocell delay adjust

only up cycle

only down cycle

up and down cycle



cycle with reinforcements at pre-set heights

cycle with start at pre-set height

top sheet cycle

possibility to set a protection password on parameters

machine diagnostic by display

monitoring of the battery charger from the display

distance from pallet 130 cm

available wrapping heights:

2000 = H 2000 mm (with film coil h500 mm)

2400 = H 2400 mm (with film coil h500 mm)

available film coil carriages:

FM : mechanical friction and manual film tension adjust

FE : electromagnetic brake and film tension adjust by control panel

PM : power pre-stretch fix 230% (other on demand) and film tension adjust by control panel

PMV : power pre-stretch adjustable up to 230% (other on demand). Separated adjust of tension and pre-stretch by control panel

